



# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 05/11/2012

Revision date: 08/02/2013

Supersedes: 12/12/2012

Version: 2.3

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : HYDRAUNYCOIL FH 51  
Product code : FH51-1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use  
Use of the substance/mixture : Mineral oil  
Function or use category : Lubricant.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

NYCO  
66 Avenue des Champs Elysées  
75366 Paris Cedex 08 - France  
T +33 (0)1 45 61 50 00  
[info@nyco.fr](mailto:info@nyco.fr) - [www.nyco.fr](http://www.nyco.fr)

#### 1.4. Emergency telephone number

Emergency number : +33 (0)1 45 42 59 59  
INRS/ORFILA (France) : 33 1 45 42 59 59

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Full text of H-phrases: see section 16

##### Classification according to Directive 67/548/EEC or 1999/45/EC

Xn; R20  
Xi; R38  
N; R51/53

Full text of R-phrases: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazardous ingredients : Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).]

Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H332 - Harmful if inhaled  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) : P261 - Avoid breathing Vapors  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective gloves, protective clothing, eye protection  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).]	(CAS No.)64742-46-7 (EC no)265-148-2 (EC index no)649-221-00-X	50 - 100	Xn; R20 Xn; R65 Xi; R38 N; R51/53
Gas oils (petroleum), hydrodesulfurized, Gasoil - unspecified, [A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulfur to hydrogen sulfide which is removed. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C13 through C25 and boiling in the range of approximately 230 °C to 400 °C (446 °F to 752 °F).]	(CAS No.)64742-79-6 (EC no)265-182-8 (EC index no)649-222-00-5	2,5 - 10	Xn; R20 Xi; R38 Xn; R65 N; R51/53
2,6-di-tert-butyl-p-cresol	(CAS No.)128-37-0 (EC no)204-881-4	0 - 2,5	N; R50/53
Phenol, isopropylated, phosphate	(CAS No.)68937-41-7 (EC no)273-066-3	0 - 1	Xn; R48/22 N; R51/53 Repr.Cat.3; R62 Repr.Cat.3; R63

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).]	(CAS No.)64742-46-7 (EC no)265-148-2 (EC index no)649-221-00-X	50 - 100	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Gas oils (petroleum), hydrodesulfurized, Gasoil - unspecified, [A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulfur to hydrogen sulfide which is removed. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C13 through C25 and boiling in the range of approximately 230 °C to 400 °C (446 °F to 752 °F).]	(CAS No.)64742-79-6 (EC no)265-182-8 (EC index no)649-222-00-5	2,5 - 10	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,6-di-tert-butyl-p-cresol	(CAS No.)128-37-0 (EC no)204-881-4	0 - 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenol,isopropylated,phosphate	(CAS No.)68937-41-7 (EC no)273-066-3	0 - 1	Repr. 2, H361fd STOT RE 2, H373 Aquatic Chronic 2, H411

Full text of R-, H- and EUH-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Seek medical advice (show the label where possible).
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of soap and water. Seek medical advice (show the label where possible).
First-aid measures after eye contact	: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice (show the label where possible).
First-aid measures after ingestion	: If swallowed: Rinse mouth. Do NOT induce vomiting. Seek medical advice (show the label where possible).

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: At high concentrations, the vapours can be irritating to the respiratory system.
Symptoms/injuries after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Eye irritation.
Symptoms/injuries after ingestion	: Possible irritation of mucous membranes and digestive tract, nausea, vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Foam. Dry powder. Carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: On burning: release of harmful/irritant gases/vapours. Carbon oxides (CO, CO <sub>2</sub> ).
Reactivity	: Stable at ambient temperature and under normal conditions of use.

### 5.3. Advice for firefighters

Precautionary measures fire	: Protective equipment.
-----------------------------	-------------------------

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
------------------	--

#### 6.1.1. For non-emergency personnel

Protective equipment	: See Headings 7 and 8.
Emergency procedures	: For a large spillage, contain the spillage by bunding.

#### 6.1.2. For emergency responders

Protective equipment	: See Headings 7 and 8.
Emergency procedures	: For a large spillage, contain the spillage by bunding.

### 6.2. Environmental precautions

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel).
-------------------------	--

### 6.4. Reference to other sections

No additional information available

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Stable at ambient temperature and under normal conditions of use.
- Precautions for safe handling : Wear suitable protective clothing. Personal protective equipment. When using do not eat, drink or smoke. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Avoid spilling the product, as this might cause falls. Provide local exhaust or general room ventilation.
- Hygiene measures : When using do not eat or drink. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in dry, cool, well-ventilated area.
- Special rules on packaging : Store in original container. Keep container closed when not in use.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Gas oils (petroleum), hydrodesulfurized, Gasoil - unspecified, [A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulfur to hydrogen sulfide which is removed. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C13 through C25 and boiling in the range of approximately 230 °C to 400 °C (446 °F to 752 °F).] (64742-79-6)**

EU	IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
EU	IOELV STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

#### **2,6-di-tert-butyl-p-cresol (128-37-0)**

United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
----------------	------------------------------	----------------------

#### 8.2. Exposure controls

- Personal protective equipment : Gloves. Safety glasses. Protective clothing.



- Hand protection : Chemical resistant gloves (according to European standard NF EN 374 or equivalent).
- Eye protection : Safety glasses with side shields.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : No personal breathing protective equipment is normally required.
- Environmental exposure controls : Do not flush into surface water or sewer system.

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -66 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 94 °C
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: < 110 kPa (1.1 bar)
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,871 kg/l @20°C
Solubility	: Material insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 14,1 mm <sup>2</sup> /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable at ambient temperature and under normal conditions of use.

#### 10.2. Chemical stability

No additional information available

#### 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

Elevated temperature.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

**Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7)**

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 1,78 mg/l/4h

#### **Phenol, isopropylated, phosphate (68937-41-7)**

LD50 oral rat	> 5000 mg/kg
---------------	--------------

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

<b>Phenol, isopropylated, phosphate (68937-41-7)</b>	
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
LD50 oral rat	> 2930 mg/kg OCDE 401
LD50 dermal rat	> 2000 mg/kg OCDE 402

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Phenol, isopropylated, phosphate (68937-41-7)</b>	
LC50 fishes 1	1,6 mg/l 96 h : Oncorhynchus mykiss
EC50 Daphnia 1	2,44 mg/l 48 h :Daphnia magna
LC50 fish 2	10,8 mg/l 96 h: Pimephales promelas

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Collect all waste in suitable and labelled containers and dispose according to local legislation.

## SECTION 14: Transport information

In accordance with ADR / RID / ADN / IMDG / ICAO / IATA

### 14.1. UN number

UN-No. : 3082

### 14.2. UN proper shipping name

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Transport document description : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), hydrotreated middle, Gasoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F)].(64742-46-7)), 9, III, (E)

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 14.3. Transport hazard class(es)

Class (UN) : 9

Hazard labels (UN) : 9



### 14.4. Packing group

Packing group (UN) : III

### 14.5. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

Hazard identification number (Kemler No.) : 90

Classification code (UN) : M6

Orange plates :



Special provision (ADR) : 274, 335, 601

Transport category (ADR) : 3

Tunnel restriction code : E

Limited quantities (ADR) : 5L

Excepted quantities (ADR) : E1

EAC code : •3Z

#### 14.6.2. Transport by sea

No additional information available

#### 14.6.3. Air transport

No additional information available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Contains no REACH candidate substance

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

# HYDRAUNYCOIL FH 51

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H332	Harmful if inhaled
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
R20	Harmful by inhalation.
R38	Irritating to skin.
R48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*