## **Technical Data Sheet**



Product Name:	Dry Film Lubricant	
Product Number:	PL470	
Product Description:	PL470 is a quick drying Molybdenum Di-Sulphide Dry Film Lubricant	
Approvals/Specifications:	<ul><li>OMat 4-70</li><li>Co-Mat 04-016</li><li>MSRR1141</li></ul>	
Performance:	PL470 has been tested for chemical resistance; quick drying and lubricity.  Resistant to Oils, Grease and Aqueous Cleaning Fluids.	
Application:		
Surface Preparation:	Refer to the instruction sheet contained within the kit and TSD 70-00-00-900-335-A06	
	Clean the blade roots of any debris using the specifically designed scraper in the kit. Degrease scraper in the kit. Degrease surfaces with IP9064-TDXL or Re-Lube Kit approved cleaner for use with PL470	
Paint Preparation:	Supplied ready for use with OMat 4-70 Series Kit Shake Bottle Vigorously for 2-5 minutes before use <b>Thinner / Reducer Addition:</b> IP9064-TDXL Thinner	
Application Method:	Refer to the instruction sheet contained with the kit and TSD 70-00-00-300-355-A06. Dip the applicator pad in the PL470 and drag	

through the blade root, which applies the dry film lubricant.

Will air dry in ambient temperatures (15-25°C) within 30 minutes. Formulated to dry below freezing point, but drying time will be

extended. Ensure free air flow to facilitate correct drying conditions.

**Drying Curing:** 

## **Technical Data Sheet**



echnical Properties:	Supply Viscosity:	3500-4500 cP @ 23°C
----------------------	-------------------	---------------------

Flash Point: 18°C

VOC Content: 584 g/l

Colour: Dark Grey / Black

Pack Size: 100ml (plastic bottles)

**Density:**  $1.34 \pm 0.02 \text{kg/l}$ 

Gloss: Semi-Matt

Thinner: IP9064-TDXL

Solvent/Clean Up: 40006

Catalyst: N / A

**Theoretical Coverage:** 6m<sup>2</sup> / Litre at 50 microns

Storage:

Highly flammable liquid: store and use in accordance with the flammable liquid regulations

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

**Disclaimer:** 

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

## **Safety Data Sheets:**

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk