## **Technical Data Sheet**



Issue 1

Product Name:	Thixotropic Dry Film Lubricant	
Product Number:	PL198	
Product Description:	Single package Thixotropic Dry Film Lubricant	
Approvals/Specifications:	<ul> <li>Rolls Royce Code: 134110</li> <li>Was previously OMat 4/20</li> </ul>	
Performance:	<ul> <li>Thixotropic Lubricant formulated to ease assembly of Aircraft Engine Components.</li> </ul>	
	<ul> <li>Designed for wet assembly applications on splinted shafts and screw threads.</li> </ul>	
	- PL198 is used on steel, light alloys and other metals, for example on the front combustion liner for the RB211.	
	- Used for thread lubrication in torque loading applications	
	- Designed for use with wet assembly	
Components:	Single Part Product. May be thinned for application using either IP985-Reducer or IP9151 Thinner. IP985-REDUCER is preferred. IP9151 is still approved for use but is no longer a preferred solvent as it triggers risk phrase R40. Other solvents may be suitable in certain circumstances	
Application:		
Surface Preparation:	Ensure that surfaces are clean and free from any grease, oil or dirt	
Paint Preparation:	One pack product – stir thoroughly before use	

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995

## **Technical Data Sheet**



Issue 1

Application Method:	Brush applied to threaded area / mating surface			
Drying Curing:	Air Dry: Allow to dry for 10 minutes before making the joint			
Technical Properties:	Supply Viscosity:	Thixotropic		
	Flash Point:	41°C		
	VOC Content:	662gm / litre		
	Colour:	Dark Grey / Black		
	Pack Size:	1 Litre		
	Density:	1.010 – 1.040kg/l		
	Gloss:	Not Applicable		
	Thinner:	IP985-REDUCER is preferred. IP9151 is still approved for use but is no longer a preferred solvent as it triggers risk phrase R40. Other solvents may be suitable in certain circumstances		
	Solvent/Clean Up:	40006		
	Catalyst:	N/A		
	Theoretical Coverage:	-		
Storage:	Highly flammable liquid: store and use in accordance with the flammable liquid regulations Shelf Life: 12 months temperate; 6 months tropical Before use, refer to Product Safety Data Sheet			
Disclaimer:	Indestructible Paint Ltd. No represent accuracy or completeness of the info Paint Ltd make no warranty or represent without information limitation any wa purpose, and no warranty or represent products sold by Indestructible Paint	The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the		
Indestructible Paint Ltd, 16-25 Pentos Drive, Sp Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4 Registered in England: 1376995	arkhill, Birmingham B1131A 4338, Ehnar Series of Corocicity Suitable to	Indestructible Paint Ltd assumes no responsibility for the particular burger. the particular purpose of any particular buyer. yent be liable for any special, incidental or		

## **Technical Data Sheet**



Issue 1

## **Safety Data Sheets:**

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995