



Safety Data Sheet

Page 1 of 8

RETAINING COMPOUND 609 BULK

MSDS-No. : 153471

V001.3

Date of issue: 08.05.2015

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: RETAINING COMPOUND 609 BULK

Intended use: Anaerobic Adhesive

Supplier:

Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 03 9724 6556

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Skin irritation	Category 2	
Serious eye irritation	Category 2A	
Skin sensitizer	Category 1	
Target Organ Systemic Toxicant - Single exposure	Category 3	respiratory tract irritation
Chronic hazards to the aquatic environment	Category 3	

Hazard pictogram:



Signal word:

Warning

Hazard statement(s):	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary Statement(s):	
Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves, clothing, eye and face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362 Take off contaminated clothing.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Classification of material Xi - Irritant

Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.
R43 May cause sensitisation by skin contact.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S23 Do not breathe vapour.
S24 Avoid contact with skin.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29 Do not empty into drains.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word:

HAZARDOUS

Section 3. Composition / information on ingredients

General chemical description: Substance
General chemical description: Mixture
Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
2-Hydroxyethyl methacrylate	868-77-9	10- 30 %
Cumene hydroperoxide	80-15-9	< 3 %
Methacrylic acid	79-41-4	< 1 %
non hazardous ingredients~		60- 100 %

Section 4. First aid measures

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Immediately flush skin with plenty of water (using soap, if available). Seek medical advice.
Eyes:	Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice.
Inhalation:	Move to fresh air. Keep warm and in a quiet place. Seek medical advice.
First Aid facilities:	Eye wash Normal washroom facilities
Medical attention and special treatment:	Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media:	Carbon dioxide, foam, powder
Decomposition products in case of fire::	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.
Special protective equipment for fire-fighters:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:	Ensure adequate ventilation. Avoid skin and eye contact. Wear appropriate personal protective equipment.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage

Precautions for safe handling:	Use only in well-ventilated areas. Avoid skin and eye contact. Wear suitable protective clothing, safety glasses and gloves. Prolonged or repeated skin contact should be avoided
---------------------------------------	--

Conditions for safe storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection**National exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
METHACRYLIC ACID 79-41-4		20	70	-	-	-	-

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.
Avoid skin-contact.

Recommended gloves include butyl rubber and neoprene.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Respiratory protection:

If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:	Green Liquid
Odor:	Mild
Specific gravity:	1.1
Boiling point:	> 150 °C (> 302 °F)
Flash point: (Tagliabue closed cup)	> 93.3 °C (> 199.94 °F)
Vapor pressure: (; 26 °C (78.8 °F))	< 6 mbar
Density:	1.1 g/cm ³
VOC content: (1999/13/EC)	< 3.00 %

Section 10. Stability and reactivity**Stability:**

Stable under recommended storage conditions.

Conditions to avoid:

Keep away from heat, ignition sources and incompatible materials.

Incompatible materials:

Reacts with strong oxidants.

Hazardous decomposition products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide.
Carbon dioxide.
Oxides of nitrogen.

Section 11. Toxicological information

Health Effects:**Ingestion:**

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin:

Causes skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

Eyes:

Causes serious eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Inhalation:

This product is irritating to the respiratory system.

Vapors are irritating to the nose, throat and respiratory tract resulting in dryness of throat and tightness in chest. Other symptoms of overexposure include headache, nausea, narcosis, fatigue and loss of appetite.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 3,000 mg/kg	dermal		rabbit	
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	
Methacrylic acid 79-41-4	LD50 LC50 Acute toxicity estimate (ATE) LD50	1,320 mg/kg 4.7 mg/l 500 mg/kg 500 - 1,000 mg/kg	oral inhalation dermal dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) Expert judgement Dermal Toxicity Screening

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	Buehler test

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	negative positive	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	160 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid 79-41-4	LC50	85 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Methacrylic acid 79-41-4	NOEC	8.2 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid 79-41-4	EC50	45 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
------------------------------	--------	----------------------	---------------	--------

2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Cumene hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide 80-15-9	2.16					
Methacrylic acid 79-41-4	0.93				22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

Section 14. Transport information**Road and Rail Transport:**

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Section 15. Regulatory information

SUSMP Poisons Schedule None

AICS: All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).

Section 16. Other information

Abbreviations/acronyms:

ADGC - Australian Dangerous Goods Code
IMDG: International Maritime Dangerous Goods code
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
STEL - Short term exposure limit
TWA - Time weighted average

Reason for issue:

Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue:

05.07.2012

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.