

**Washprimer
ACC WP 4004**



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Washprimer
ACC WP 4004
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Printing . For professional use only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:** AirChem Consumables Fzco
PO Box: 261503
Jebble Ali Free Zone, Dubai-UAE
Phone.: +971 -4- 881 8084
Fax: +971 -4- 881 6022
- 1.4 Emergency telephone number:** +971 -4- 881 8084

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) n° 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411
Carc. 1B: Carcinogenicity, Category 1B, H350
Flam. Liq. 3: Flammable liquids, Category 3, H226
Repr. 1A: Reproductive toxicity, Category 1A , H360Df
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

- 2.2 Label elements:**
CLP Regulation (EC) n° 1272/2008:
Danger



Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
Carc. 1B: H350 - May cause cancer
Flam. Liq. 3: H226 - Flammable liquid and vapour
Repr. 1A: H360Df - May damage the unborn child. Suspected of damaging fertility.
STOT SE 3: H336 - May cause drowsiness or dizziness

Precautionary statements:

P201: Obtain special instructions before use
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280: Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
P308+P313: IF exposed or concerned: Get medical advice/attention
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking
EUH201: Contains lead. Should not be used on surfaces liable to be chewed or sucked by children
EUH208: Contains 2-hydroxyethyl methacrylate, Formaldehyde. May produce an allergic reaction

Substances that contribute to the classification

Butyl Acetate; Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7; Lead sulfochromate yellow; Solvente Nafta (petróleo) fracção aromática leve

Additional Labelling (Annex XVII, REACH):

Restricted to professional users

**Washprimer
ACC WP 4004**



SECTION 2: HAZARDS IDENTIFICATION (continue)

2.3 Other hazards:

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, aggregates and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:


Identification	Chemical name/Classification	Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	Butyl Acetate Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	ATP CLP00 10 - <25 %
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	ATP ATP01 2,5 - <10 %
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336 - Danger	ATP ATP01 2,5 - <10 %
CAS: 1344-37-2 EC: 215-693-7 Index: 082-009-00-X REACH: 01-2119502446-46-XXXX	Lead sulfochromate yellow Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Carc. 1B: H350; Repr. 1A: H360Df; STOT RE 2: H373 - Danger	ATP ATP01 2,5 - <10 %
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: Non-applicable	Solvente Nafta (petróleo) fraccão aromática leve Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	Self-classified 1 - <2,5 %
CAS: 95-63-6 EC: 202-436-9 Index: 601-043-00-3 REACH: 01-2119472135-42-XXXX	1,2,4-trimethylbenzene Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	ATP CLP00 <1 %
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	Acetone Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	ATP CLP00 <1 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene (mixture of isomers) Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	ATP CLP00 <1 %
CAS: 868-77-9 EC: 212-782-2 Index: 607-124-00-X REACH: 01-2119490169-29-XXXX	2-hydroxyethyl methacrylate Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	ATP CLP00 <1 %
CAS: 50-00-0 EC: 200-001-8 Index: 605-001-00-5 REACH: 01-2119488953-20-XXXX	Formaldehyde Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Carc. 1B: H350; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	ATP ATP06 <1 %
CAS: 80-62-6 EC: 201-297-1 Index: 607-035-00-6 REACH: 01-2119452498-28-XXXX	Methyl methacrylate Regulation 1272/2008 Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	ATP CLP00 <1 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	Ethylbenzene Regulation 1272/2008 Acute Tox. 4: H332; Flam. Liq. 2: H225 - Danger	Self-classified <1 %
CAS: 7664-38-2 EC: 231-633-2 Index: 015-011-00-6 REACH: 01-2119485924-24-XXXX	Phosphoric Acid Regulation 1272/2008 Skin Corr. 1B: H314 - Danger	ATP CLP00 <1 %

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continue)

Identification	Chemical name/Classification		Concentration
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	Toluene	ATP CLP00	<1 %
Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger 		

To obtain more information on the risk of the substances consult sections 8, 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as dangerous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 6: ACCIDENTAL RELEASE MEASURES (continue)

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
	IOELV (8h)	IOELV (STEL)	Year
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	50 ppm	275 mg/m ³	
	100 ppm	550 mg/m ³	
			2014
Lead sulfochromate yellow CAS: 1344-37-2 EC: 215-693-7	0,15 mg/m ³		
			2014

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Identification	Environmental limits		
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	IOELV (8h)	20 ppm	100 mg/m ³
	IOELV (STEL)		
	Year	2014	
Acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m ³
	IOELV (STEL)		
	Year	2014	
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
	Year	2014	
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	IOELV (8h)	50 ppm	
	IOELV (STEL)	100 ppm	
	Year	2014	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m ³
	IOELV (STEL)	200 ppm	884 mg/m ³
	Year	2014	
Phosphoric Acid CAS: 7664-38-2 EC: 231-633-2	IOELV (8h)		1 mg/m ³
	IOELV (STEL)		2 mg/m ³
	Year	2014	
Toluene CAS: 108-88-3 EC: 203-625-9	IOELV (8h)	50 ppm	192 mg/m ³
	IOELV (STEL)	100 ppm	384 mg/m ³
	Year	2014	

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	275 mg/m ³	Non-applicable
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	16171 mg/kg	Non-applicable
	Inhalation	100 mg/m ³	100 mg/m ³	100 mg/m ³	100 mg/m ³
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,3 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4,9 mg/m ³	Non-applicable
Formaldehyde CAS: 50-00-0 EC: 200-001-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	240 mg/kg	Non-applicable
	Inhalation	Non-applicable	1 mg/m ³	9 mg/m ³	0,5 mg/m ³
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	13,67 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	208 mg/m ³	208 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Phosphoric Acid CAS: 7664-38-2 EC: 231-633-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	2 mg/m ³	Non-applicable	1 mg/m ³
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859,7 mg/m ³	859,7 mg/m ³	102,34 mg/m ³	102,34 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	Non-applicable
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
	Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,9 mg/m ³	Non-applicable
Formaldehyde CAS: 50-00-0 EC: 200-001-8	Oral	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	102 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3,2 mg/m ³	0,1 mg/m ³
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	74,3 mg/m ³	104 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Phosphoric Acid CAS: 7664-38-2 EC: 231-633-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,73 mg/m ³
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³

PNEC:

Identification					
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,0903 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L	
	Soil	0,29 mg/kg	Marine water	0,0635 mg/L	
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg	
Lead sulfochromate yellow CAS: 1344-37-2 EC: 215-693-7	STP	Non-applicable	Fresh water	0,1 mg/L	
	Soil	Non-applicable	Marine water	0,01 mg/L	
	Intermittent	1 mg/L	Sediment (Fresh water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	STP	2,41 mg/L	Fresh water	0,12 mg/L	
	Soil	2,34 mg/kg	Marine water	0,12 mg/L	
	Intermittent	0,12 mg/L	Sediment (Fresh water)	13,56 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	13,56 mg/kg	

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Identification				
Acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L
	Soil	29,5 mg/kg	Marine water	1,06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	STP	10 mg/L	Fresh water	0,482 mg/L
	Soil	0,476 mg/kg	Marine water	0,482 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	3,79 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,79 mg/kg
Formaldehyde CAS: 50-00-0 EC: 200-001-8	STP	0,19 mg/L	Fresh water	0,47 mg/L
	Soil	0,21 mg/kg	Marine water	0,47 mg/L
	Intermittent	4,7 mg/L	Sediment (Fresh water)	2,44 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	2,44 mg/kg
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	STP	10 mg/L	Fresh water	0,94 mg/L
	Soil	1,47 mg/kg	Marine water	0,94 mg/L
	Intermittent	0,94 mg/L	Sediment (Fresh water)	5,74 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13,61 mg/L	Fresh water	0,68 mg/L
	Soil	2,89 mg/kg	Marine water	0,68 mg/L
	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place



As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.



D.- Ocular and facial protection

- CONTINUED ON NEXT PAGE -





**Washprimer
ACC WP 4004**





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006 EN ISO 20344:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	35,12 % weight
V.O.C. density at 25 °C:	347,65 kg/m ³ (347,65 g/L)
Average carbon number:	6,64
Average molecular weight:	119,8 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Color:	Characteristic
Odor:	Solvent

Volatility:

Boiling point at atmospheric pressure:	136 °C
Vapour pressure at 25 °C:	4693 Pa
Vapour pressure at 50 °C:	12112 Pa (12 kPa)
Evaporation rate at 25 °C:	Non-applicable *

Product description:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continue)

Density at 25 °C:	940 - 1040 kg/m ³
Relative density at 25 °C:	1,057
Dynamic viscosity at 25 °C:	1708,88 - 1603,04 cP
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 °C:	Non-applicable *
Partition coefficient n-octanol/water 25 °C:	Non-applicable *
Solubility in water at 25 °C:	Non-applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	32 °C
Autoignition temperature:	294 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

9.2 Other information:

Surface tension at 25 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Avoid direct impact	Not applicable	Not applicable

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 11: TOXICOLOGICAL INFORMATION (continue)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

B- Inhalation:

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes:

- Contact with the skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
- Mutagenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: May damage the unborn child. Suspected of damaging fertility.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensibilizing effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensibilizing effects. For more information see section 3.

F- Specific target organ toxicity (STOT)-time exposure:

Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of concentration.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	LD50 oral	5050 mg/kg	Rat
	LD50 dermal	3000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 11: TOXICOLOGICAL INFORMATION (continue)

Identification	Acute toxicity		Genus
	Route	Dose	
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation	28,1 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	LD50 oral	3400 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (4 h)	Rat
Phosphoric Acid CAS: 7664-38-2 EC: 231-633-2	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	2470 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h)	Rat
Lead sulfochromate yellow CAS: 1344-37-2 EC: 215-693-7	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Formaldehyde CAS: 50-00-0 EC: 200-001-8	LD50 oral	100 mg/kg	Rat
	LD50 dermal	270 mg/kg	Rabbit
	LC50 inhalation	1,1 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Specie	Genus
	Route	Dose		
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
Lead sulfochromate yellow CAS: 1344-37-2 EC: 215-693-7	LC50	0,1 - 1 mg/L (96 h)		Fish
	EC50	0,1 - 1 mg/L		Crustacean
	EC50	0,1 - 1 mg/L		Algae
Solvente Nafta (petróleo) fraccão aromática leve CAS: 64742-95-6 EC: 265-199-0	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	LC50	7,72 mg/L (96 h)	Pimephales promelas	Fish
	EC50	6,14 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	23,5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 12: ECOLOGICAL INFORMATION (continue)

Identification	Acute toxicity		Specie	Genus
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LC50	13,5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0,6 mg/L (96 h)	Gammarus lacustris	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	LC50	227 mg/L (96 h)	Pimephales promelas	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
Formaldehyde CAS: 50-00-0 EC: 200-001-8	LC50	100 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	42 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	LC50	191 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	69 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	170 mg/L (96 h)	Selenastrum capricornutum	Algae
Phosphoric Acid CAS: 7664-38-2 EC: 231-633-2	LC50	Non-applicable		
	EC50	4,6 mg/L (12 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Toluene CAS: 108-88-3 EC: 203-625-9	LC50	13 mg/L (96 h)	Carassius auratus	Fish
	EC50	11,5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BOD5	0.19 g O2/g	Concentration	Non-applicable
	COD	0.44 g O2/g	Period	Non-applicable
	BOD5/COD	0.43	% Biodegradable	Non-applicable
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.43	% Biodegradable	18 %
Acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.96	% Biodegradable	96 %
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	95 %
Formaldehyde CAS: 50-00-0 EC: 200-001-8	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	0.74	% Biodegradable	92 %
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94,3 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2.5 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 12: ECOLOGICAL INFORMATION (continue)

Identification	Bioaccumulation potential	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1,78
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0,43
	Potential	Low
Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	BCF	154
	Pow Log	3,78
	Potential	High
Acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0,24
	Potential	Low
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2,77
	Potential	Low
2-hydroxyethyl methacrylate CAS: 868-77-9 EC: 212-782-2	BCF	3
	Pow Log	0,47
	Potential	Low
Formaldehyde CAS: 50-00-0 EC: 200-001-8	BCF	3
	Pow Log	0,35
	Potential	Low
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BCF	7
	Pow Log	1,38
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3,15
	Potential	Low
Toluene CAS: 108-88-3 EC: 203-625-9	BCF	13
	Pow Log	2,73
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	24780 N/m (25 °C)	Moist soil	Non-applicable
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Koc	537	Henry	6,242E+2 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	29190 N/m (25 °C)	Moist soil	Yes
Acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,929E+0 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	23040 N/m (25 °C)	Moist soil	Yes
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	5,249E+2 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Formaldehyde CAS: 50-00-0 EC: 200-001-8	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	14160 N/m (25 °C)	Moist soil	Non-applicable
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	25510 N/m (25 °C)	Moist soil	Non-applicable

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 12: ECOLOGICAL INFORMATION (continue)

Identification	Absorption/desorption		Volatility	
	Koc	520	Henry	7,984E+2 Pa·m ³ /mol
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Conclusion	Moderate	Dry soil	Yes
	Surface tension	28590 N/m (25 °C)	Moist soil	Yes
Toluene CAS: 108-88-3 EC: 203-625-9	Koc	178	Henry	6,728E+2 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	27930 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP7 Carcinogenic, HP10 Toxic for reproduction

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: II
14.5 Dangerous for the environment: Yes
14.6 Special precautions for user
 Special regulations: 163, 367, 640E, 650
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 37-14:

- CONTINUED ON NEXT PAGE -

**Washprimer
ACC WP 4004**



SECTION 14: TRANSPORT INFORMATION (continue)



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: II
14.5 Dangerous for the environment: Yes
14.6 Special precautions for user
 Special regulations: 163, 223, 944, 955
 EmS Codes: F-E, S-E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: II
14.5 Dangerous for the environment: Yes
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Lead sulfochromate yellow
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Lead sulfochromate yellow (5/21/2015)
 Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Formaldehyde (excluded for the product type 1, 4, 5, 6, 9, 11, 12, 13, 20, 21)
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable
Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):

**Washprimer
ACC WP 4004**



SECTION 15: REGULATORY INFORMATION (continue)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- “whoopee” cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Product classified hazardous under the CMR. Sale and distribution to the general public is prohibited. Due to its CMR category, it is essential to apply the specific measures for workplace hazard prevention covered in articles 4 and 5 of the 90/394/EC Directive and later modifications.

Leather articles coming into contact with the skin shall not be placed on the market where they contain chromium VI in concentrations equal to or greater than 3 mg/kg (0,0003 % by weight) of the total dry weight of the leather.

Articles containing leather parts coming into contact with the skin shall not be placed on the market where any of those leather parts contains chromium VI in concentrations equal to or greater than 3 mg/kg (0,0003 % by weight) of the total dry weight of that leather part.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 453/2010)

Modifications related to the previous security card which concerns the ways of managing risks. :

Content of the 3rd section presenting modifications:

- 1,2,4-trimethylbenzene (95-63-6): REACH Number
- 2-hydroxyethyl methacrylate (868-77-9): REACH Number
- Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 (64742-95-6): REACH Number

Texts of the legislative phrases mentioned in section 2.:

H336: May cause drowsiness or dizziness

H411: Toxic to aquatic life with long lasting effects

H350: May cause cancer

H360Df: May damage the unborn child. Suspected of damaging fertility.

H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3.:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) n° 1272/2008:

**Washprimer
ACC WP 4004**



SECTION 16: OTHER INFORMATION (continue)

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Acute Tox. 4: H332 - Harmful if inhaled
Aquatic Acute 1: H400 - Very toxic to aquatic life
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Carc. 1B: H350 - May cause cancer
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Muta. 2: H341 - Suspected of causing genetic defects
Repr. 1A: H360Df - May damage the unborn child. Suspected of damaging fertility.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
STOT SE 3: H335 - May cause respiratory irritation
STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method
Aquatic Chronic 2: Calculation method
Carc. 1B: Calculation method
Repr. 1A: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>
<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

- ADR: European agreement concerning the international carriage of dangerous goods by road
-IMDG: International maritime dangerous goods code
-IATA: International Air Transport Association
-ICAO: International Civil Aviation Organisation
-COD: Chemical Oxygen Demand
-BOD5: 5-day biochemical oxygen demand
-BCF: Bioconcentration factor
-LD50: Lethal Dose 50
-CL50: Lethal Concentration 50
-EC50: Effective concentration 50
-Log-POW: Octanol-water partition coefficient
-Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -