

# ACC 4420-4

<b>Product Group</b>	Odorless cleaning solvent
<b>Description</b>	ACC 4420-4 is a mixture of aliphatic petroleum solvents and has replaced chlorinated solvents like perchloroethylene, trichloroethylene, methylene chloride, white spirit, aromatic naphtha and similar solvents
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>Very low odor (negligible)</li> <li>Low toxicity and hazards</li> <li>No residue</li> <li>Clear liquid</li> <li>High flash point ( 53°C)</li> <li>Safe on steel and aluminum alloys, rubber, synthetic rubber and insulating materials.</li> <li>Suitable for use in confined areas with poor ventilation.</li> </ul>
<b>Application</b>	<ul style="list-style-type: none"> <li>Use as received.</li> <li>Apply, at room temperature, by dip, spray gun, brush, wipe</li> <li>Change cloth frequently.</li> <li>Remove residues with clean cloth.</li> <li>Can be used in agitated dip tank and ultrasonic equipment as solvent cleaner to clean all kinds of contaminations including greases, waxes, polishes, oils, rust preventives, inks, enamels, etc. from steel, iron, aluminum or other equipment.</li> </ul>
<b>Toxicity and Hazards</b>	<ul style="list-style-type: none"> <li>Before use always refer to <b>MATERIAL SAFETY DATA SHEET</b> for precautionary, handling and first aid information.</li> <li>Dispose of ACC 4420-4 per applicable regulations. Refer to <b>MATERIAL SAFETY DATA SHEET</b> for additional disposal information.</li> </ul>
<b>Storage</b>	Store containers at temperatures between 5-40°C.
<b>Shelf life/Packing</b>	24 Months/ 25 KG Pail

**Notice**

The provided information in this document is given in good faith and based on our current knowledge. It is indicative information only and never binding. It must on no account be used as a substitute for necessary preliminary tests that must ensure the suitability of our product. TDS 4420-4 – 12/2018