



SAFETY DATA SHEET

High Heat Aluminium Air Dry Touch Up

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name High Heat Aluminium Air Dry Touch Up
Product number IP9138-R1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.
Uses advised against Keep away from food, drink and animal feeding stuffs.

1.3. Details of the supplier of the safety data sheet

Supplier INDESTRUCTIBLE PAINT LTD
 19-25 Pentos Drive
 Sparkhill
 Birmingham
 England
 B11 3TA
 Tel +44(0)121 702 2485
 Fax +44(0)121 778 4338
 sales@indestructible.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)7772968830

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Muta. 1B - H340 Carc. 1B - H350
 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xi;R38,R41. R43. R10,R52/53,R67.

2.2. Label elements

Pictogram



Signal word

Danger

High Heat Aluminium Air Dry Touch Up

Hazard statements	<p>H226 Flammable liquid and vapour. H412 Harmful to aquatic life with long lasting effects. H315 Causes skin irritation. H318 Causes serious eye damage. H340 May cause genetic defects. H350 May cause cancer. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.</p>
Precautionary statements	<p>P201 Obtain special instructions before use. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P501 Dispose of contents/container in accordance with national regulations.</p>
Supplemental label information	<p>RCH002b For professional users only.</p>
Contains	<p>1-Butanol,titanium (4+) salt, BUTYL ACETATE -norm, EPOXY RESIN (Number average MW ≤700), 1-METHOXY-2-PROPANOL, Solvent naphtha (petroleum), light arom (>0.1% Benzene)</p>
Supplementary precautionary statements	<p>P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 IF exposed or concerned: Get medical advice/attention. P310 Immediately call a POISON CENTER/doctor. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.</p>

2.3. Other hazards

None Identified

SECTION 3: Composition/information on ingredients

3.2. Mixtures

High Heat Aluminium Air Dry Touch Up

1-Butanol,titainium (4+) salt		40-60%
CAS number: 5593-70-4		EC number: 227-006-8
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	Xi;R41,R38.	
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H335, H336		
BUTYL ACETATE -norm		10-20%
CAS number: 123-86-4		EC number: 204-658-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R66 R67	
STOT SE 3 - H336		
ALUMINIUM POWDER (STABILIZED)		10-20%
CAS number: 7429-90-5		EC number: 231-072-3
		REACH registration number: 01-2119529243-45-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Not Classified	F;R11,R15	
EPOXY RESIN (Number average MW ≤700)		5-10%
CAS number: 25068-38-6		EC number: 500-033-5
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
XYLENE		5-10%
CAS number: 1330-20-7		EC number: 215-535-7
		REACH registration number: 01-2119488216-32-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
1-METHOXY-2-PROPANOL		3-<5%
CAS number: 107-98-2		EC number: 203-539-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R67	
STOT SE 3 - H336		

High Heat Aluminium Air Dry Touch Up

White Spirit, D40 (Benzene <0.1%, Aromatics <2%)	3-<5%
CAS number: —	
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R66.
Solvent naphtha (petroleum), light arom (>0.1% Benzene)	3-<5%
CAS number: 64742-95-6 EC number: 265-199-0	
Classification Flam. Liq. 3 - H226 Muta. 1B - H340 Carc. 1B - H350 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R37. N;R51/53. R10.
BUTANOL-norm	< 1%
CAS number: 71-36-3 EC number: 200-751-6	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R22 Xi;R37/38,R41 R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information Effects may be delayed. Keep affected person under observation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

High Heat Aluminium Air Dry Touch Up

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Avoid contact with oxidising agents.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ALUMINIUM POWDER (STABILIZED)

High Heat Aluminium Air Dry Touch Up

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³

Sk

BUTANOL-norm

Short-term exposure limit (15-minute): WEL 50 ppm 154 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Sk = Can be absorbed through skin.

Ingredient comments WEL = Workplace Exposure Limits

BUTYL ACETATE -norm (CAS: 123-86-4)

Ingredient comments WEL = Workplace Exposure Limits

XYLENE (CAS: 1330-20-7)

Ingredient comments WEL = Workplace Exposure Limits

White Spirit, D40 (Benzene <0.1%, Aromatics <2%)

Ingredient comments WEL = Workplace Exposure Limits

Indestructible PMA dnu

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

High Heat Aluminium Air Dry Touch Up

Hygiene measures	Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Silver.
Odour	Characteristic.
Flash point	24 - 27°C CC (Closed cup).
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 8 g/m ³
Relative density	1.04 g/ml @ 23°C
Solubility(ies)	insoluble water @ 23°C

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 355 g/litre.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	No particular stability concerns.
------------------	-----------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
---	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.
---------------------------	--------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	This product is toxic.
------------------------------	------------------------

Acute toxicity - dermal

ATE dermal (mg/kg)	16,436.31
---------------------------	-----------

Acute toxicity - inhalation

High Heat Aluminium Air Dry Touch Up

ATE inhalation (gases ppm) 67,239.45

ATE inhalation (vapours mg/l) 164.36

ATE inhalation (dusts/mists mg/l) 22.41

General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Harmful in contact with skin. Irritating to skin.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

SECTION 12: Ecological Information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity Avoid releasing into the environment.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

High Heat Aluminium Air Dry Touch Up

UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

High Heat Aluminium Air Dry Touch Up

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	19/04/2016
Revision	6
Risk phrases in full	R10 Flammable. R20/21 Harmful by inhalation and in contact with skin. R36/38 Irritating to eyes and skin. R37 Irritating to respiratory system. R38 Irritating to skin. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H340 May cause genetic defects. H350 May cause cancer. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.